



The 162 CB is designed to identify and trace wires or cables within a group without damaging the insulation.

Filter Probe

- Works with any Tone Generator to identify wires.
- Volume control for increasing sensitivity and adjustable to suit work environment.
- 2 operation modes: Filter on / Filter off.
- The auto-off function (5 minutes) prevents battery consumption.
- Power supply is available in any 9V battery with a life of approximately 50 hours.
- A phone jack is designed for headset or handset.
- Flashlight function.

Tone Generator

- Tone Generator is a great tool for locating and identifying cable pairs or individual conductors.
- 162 CB-G doesn't only provide the function of a tone generator, but also serves as a continuity and polarity tester.
- A tone selector switch located inside the unit for selection of the fast tone or the slow tone.
- Two bi-colored LEDs for Line1 and Line 2 indication of the polarities of the telephone lines.
- The unit has alligator type terminals, a modular cable of 4 conductors with a strong connector.
- The tone and continuity functions are only applied to Line1. (Modular connector)

Specifications

Filter Probe (162 CB-A)

Operation mode:	• Filter on (avoids interference of 50Hz/60Hz) • Filter off
Receiver distance:	< 50cm
Sensitivity control:	✓
Probe tip:	Fixed
Power source:	9V battery × 1
Dimensions:	250(L) × 39(W) × 38(D)mm
Weight:	Approx. 180g (battery included)

Tone Generator (162 CB-G)

Wave form:	Square Wave
Frequency:	1kHz ± 15%
Over voltage protection:	80V DC
Alternating tone:	Fast and Slow
Connection:	• RJ11 connector, alligator clip x 2, • RJ45 connector (optional)
Power source:	9V battery × 1
Dimensions:	86(L) × 63(W) × 26(D)mm
Weight:	Approx. 130g (battery included)

General

Operating temp. & humidity:	0°C~40°C, 80% Max
Storage temp. & humidity:	-10°C~50°C, 80% Max
Safety standard:	EN 61326-1. EN 61000-4-2 EN 61000-4-3
Accessories:	Instruction manual. Soft pouch. Batteries.

