



Model 183 CB

Cable Tracer



Cable Tracer

- Trace wires or cables.
- Volume control.
- Tip & Ring identification.
- 2 bi-colored LEDs (Line 1 & Line 2).
- Tone speed selection : Fast & Slow.
- A phone jack is designed for headset or handset. (Amplifier probe)

Phone Tester

- Continuity and resistance testing for voltage-free objects.
- Check direct and alternating voltages.
- Testing capacitors.
- Testing diodes.
- Power ON/OFF switch.
- The indication of the LED lamp and the sound of the buzzer can occur at the same time.
- The LED indication for Power ON status.



Cable Tracer and Test-Phone Generator

Specifications

Tone Generator

Wave form:	Square Wave
Frequency:	1kHz $\pm$ 15%
Over voltage protection:	80V DC
Single tone:	—
Alternating tone:	Fast and Slow
Connection:	RJ11 connector, alligator clip x 2
Power source:	1.5V (AA) $\times$ 6
Dimensions:	143(L) $\times$ 74.5(W) $\times$ 33.6(D)mm
Weight:	Approx. 318g (battery included)

Amplifier Probe

Frequency:	1Hz~12kHz
Receiver distance:	< 50cm
Sensitivity control:	$\sqrt$
Probe tip:	Fixed
Power source:	9V(6F22) $\times$ 1
Dimensions:	230(L) $\times$ 56(W) $\times$ 27(D)mm
Weight Approx.:	125g (battery included)

Phone Tester

Loud speaker:	$\sqrt$
Continuity testing:	$\sqrt$
Checking resistance:	$\sqrt$
ACV/DCV checking:	$\sqrt$
Checking capacitors:	$\sqrt$
Checking diodes:	$\sqrt$

General

Operating temp. & humidity:	0 $^{\circ}$ ~40 $^{\circ}$ C, 80% Max.
Storage temp. & humidity:	-10 $^{\circ}$ ~50 $^{\circ}$ C, 80% Max.

Safety standard:	EN 61326-1. EN 55011. EN 6100-4-2. EN 6100-4-3.
------------------	--

Accessories:	Instruction manual. Test leads. Carry case. Batteries.
--------------	---