




Model H2706 IM

Audio Impedance Tester



CE



AL-24-5



AL-21C2-4

Features

- True measurement of speaker systems actual impedance at 1kHz.
- Three test ranges (20Ω / 200Ω / 2000Ω) allow testing of home theater and commercial sound systems.
- Measures transformer impedances.
- Battery operated.
- Low battery indication.
- Data hold function.
- Timer function for continuous hands free operation.
- The timer can last about 3-5 minutes when users press.
- TEST ON/OFF button.

Specifications

Measuring ranges: 0-20Ω / 0-200Ω / 0-2000Ω

Test frequency: 1kHz

Accuracy: 20Ω: $\pm 2\%rdg \pm 2dgt$ or $\pm 0.1\Omega$, which is greater.
200Ω / 2000Ω: $\pm 2\%rdg \pm 2dgt$

Low battery indication:  Symbol appears on the display

Data hold indication:  Symbol appears on the display

Display: LCD 3½ digit (2000 counts)

General

Dimensions: 205(L) × 90(W) × 55(D)mm

Weight (battery included): Approx. 530g

Power source: 1.5V (AA) × 6

Safety standard: EN 61010-1 CAT III 300V, EN 61326-1.

Accessories: Instruction manual,
Test leads,
Carry case,
Batteries.