



Model HST-3502

Digital Multimeter



Specification

DC Voltage (Input impedance: 10MΩ)

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200mV	240mV	100μV			DC 500V
2V	2.4V	1mV			AC 350V
20V	24V	10mV	±(1%rdg+1dgt)	±3%F.S.	DC 1200V
200V	240V	100mV			AC 800V
600V	600V	1V			

AC Voltage (Input impedance: 10MΩ)

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200mV	240uA	100μV			DC 500V
2V	2.4V	1mV			AC 350V
20V	24V	10mV	±(1%rdg+5dgt)	±3%F.S.	DC 1200V
200V	240V	100mV			AC 800V
600V	600V	1V	±(1.5rdg+5dgt)		

DC Current

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200uA	240uA	100nA			
2mA	2.4mA	1μA			
20mA	24mA	10μA	±(1%rdg+5dgt)	±3%F.S.	800mA
200mA	240mA	100μA			
10A	10A	10mA	±(2%rdg+3dgt)		10A

AC Current

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200uA	240uA	100nA			
2mA	2.4mA	1μA			
20mA	24mA	10μA	±(1%rdg+5dgt)	±3%F.S.	800mA
200mA	240mA	100μA			
10A	10A	10mA	±(2%rdg+3dgt)		10A

Features

- 3½ digit, high contrast LCD, with a maximum display of 1999
- Automatic polarity indication, zero adjustment
- Low battery (BAT) indication
- Over range indication: highest digit of (1) or (-1)
- EN 61010-1 CAT III 600V, EN 61326-1

ANALOG DISPLAY

- Large 90° wide and 84mm long mirror scale. (adapted to digital, analogue maximum indication 2400)
- Shock and vibration resistant TAUT BAND movement
- Pointer can be selected to either left-hand zero (normal mode) or center zero (galvo-mode)
- In galvo-mode pointer deflects right to indicate positive polarity and left to indicate negative polarity
- Automatic center zero and ohm zero
- Dimensions: 175(L) × 109(W) × 44(D)mm

Resistance

Range	Analog Maximum	Resolution Digital	Accuracy		Protection
			Digital	Analog	
200Ω	5kΩ	100mΩ		±4%arc	
2kΩ	50kΩ	1mΩ	±(1%rdg+5dgt)	-10Ω	
20kΩ	500kΩ	10Ω			50V DC
200kΩ	5MΩ	100Ω		±4%arc	
2000kΩ	50MΩ	1kΩ			
20MΩ	500MΩ	10kΩ	±(1.5%rdg+5dgt)		

Capacitance

Range	Analog Maximum	Resolution Digital	Accuracy		Test Voltage
			Digital	Analog	
2000pF	2400pF	1pF			
20nF	24nF	10pF			
200nF	240nF	100pF	±(3%rdg+10dgt)	±5%F.S.	50mV
2uF	2.4nF	1nF			400Hz
20uF	24uF	10nF			

Instant Continuity

Range	Analog Maximum	Resolution Digital	Continuity Indication	Open Voltage
200Ω	5kΩ	100mΩ	Built Buzzer sounds when Resistance is less than 40Ω	3.2V MAX

Frequency

Range	Analog Maximum	Resolution Digital	Accuracy		Test Voltage
			Digital	Analog	
2000Hz	2400Hz	1Hz	±(2%rdg+3dgt)	±3%F.S.	350Vrms

Diode Test

Test Current: 3.0 ± 0.6mA
Test Voltage: 3.2V Max.

hFE Test

Base DC Current: 10μA
Vce: 2.8 ± 0
hFE: 1000